

CHAIN & CABLE LUBRICANT & PROTECTANT

- * Contains Moly
- * Penetrates * Lubricates
- * Forms Protective Rust Barrier

FOR USE ON:

- * Chains * Cables * Sprockets * Hoists
- * Link and Roller Assemblies * Power Drives * Chain Saws
- * Material Handling Equipment
- * Road and Construction Machinery

FEATURES:

- ☞ Thick foam clings to vertical surfaces ... As foam breaks, product penetrates into wire rope, link, and roller mechanisms
- ☞ Recommended for use in severe climatic conditions
- ☞ Provides resistance to wear... Extreme pressure capability
- ☞ Will not break down under high temperatures

Directions:

1. Spray 8-10 inches from surface.
2. Allow to penetrate.
3. Second coat gives additional protection.

Danger: Extremely flammable. Harmful or fatal if inhaled or swallowed. Eye and skin irritant. Contant under pressure. Carefully read cautions. Do not spray near heat, sparks or open flame.

Contains: Naphthenic Oil (CAS #64742-52-5), Propane (CAS #74-98-6), Isobutane (CAS #75-28-5), n-Butane (CAS #106-97-8), Residual Oil (CAS #64742-62-7).

First Aid: If swallowed, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY. Use with adequate ventilation. Avoid frequent or prolonged contact with skin and eyes. For skin contact, wash with soap and water. Provide oxygen or fresh air if overcome by vapor. Do not puncture or incinerate (burn) container. Do not store at temperatures above 120 deg. F (50 deg. C). Do not place near source of heat, radiator or in direct sunlight. High temperatures may cause the container to burst. If sprayed in eyes, flush thoroughly with water for 15 minutes. Get medical help.

Read Material Safety Data Sheet before using.

KEEP OUT OF REACH OF CHILDREN

Made in U.S.A.

C-580-A

NET WEIGHT 16 oz. (1 lb.)(463 g.)