

DRY-MOLY LUBE

- Lubricant • Release Agent
- Anti-Seize • Oil-Free

USES:

- * Foundries * Engine Rebuilders * Chemical Plants
- * Paper Converting * High Speed Gears and Chains
- * Wire Drawing * Conveyors * Bearings * Pump Assemblies

FEATURES:

- * Temperature range - 110° F to 1,000° F.
- * Very low coefficient of friction
- * Chemically inert to water, oil, alkalies and many acids
- * Will not attract dust
- * Burnishes into metal for excellent anti-seize and anti-friction properties

DIRECTIONS

1. Clean and dry surface to be sprayed.
2. Hold can 8 to 10 inches from surface.
3. Spray thin even coat.

IMPORTANT

Invert can and clear valve after use.

DANGER! - Do not spray near heat, sparks, or open flame.

Contains: Perchloroethylene (CAS #127-18-4), Isopropanol (CAS #67-63-0), Toluene (CAS # 108-88-3), Acetone (CAS #67-64-1), Molybdenum Disulfide (CAS #1317-33-5), Propane (CAS #74-98-6), Isobutane (CAS #75-28-5), n-Butane (CAS #106-97-8).

If swallowed, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY. Use with adequate ventilation. Avoid frequent or prolonged contact with skin and eyes. For skin contact, wash with soap and water. Provide oxygen or fresh air if overcome by vapor. Do not puncture or incinerate (burn) container. Do not store at temperatures above 120° F (50° C). Do not place near source of heat, radiator or in direct sunlight. High temperatures may cause the container to burst. If sprayed in eyes, flush thoroughly with water for 15 minutes. Get medical help. Read Material Safety Data Sheet before using. **KEEP OUT OF REACH OF CHILDREN**

Made in U.S.A.

C-590-A

CIM Supply, Inc. Tom Bing, Jr., 4813 Sardis Road, New Kensington, PA 15068
Tel: (724) 335-1798 Fax: (724) 337-0788 E-Mail: tombing@cimsupply.com
www.cimsupply.com