

# NO-WAY

## *Metal Parts Protector*

- *Long Term Rust & Corrosion Protectant*

- *Amber-Flex Dust*
- *Resistant Coating*

### USE FOR:

- Tools ● Dies ● Valves ● Drill Pipe ● Bearings
- Precision Machines Surfaces ● Cables
- Chains ● Stampings ● Housing ● Jigs
- All Exposed Metal Parts

### Features:

- Non greasy flex film protects against atmospheric or salt spray rust & corrosion
  - Excellent long term storage for all metal parts... Indoors or outdoors
  - Will prevent further rusting & pitting when sprayed over existing rusted parts
- Coating is flexible...will expand and contact with all metal surfaces uniformly...will not flake, peel, check, or crack
  - Easily removed with safety solvent degreaser
- Conforms to Military Specifications MIL-C-16173D and MIL-C-83933A, Corrosion Preventives

### DIRECTIONS:

- 1) Clean surfaces to bare metal.
- 2) Spray even coat over entire surface if needed, second coat may be applied in 5 minutes.
- 3) Coating will set up in 2 to 3 hours.

**Danger:** Do not spray near heat, sparks or open flames. Contains Hexane (CAS #110-54-3), Aliphatic Petroleum Distillates (CAS #8052-41-3), Acetone (CAS #67-64-1), Propane (CAS #74-98-6), Clay (CAS #1302-78-9), Isobutane (CAS #75-28-5), n-Butane (CAS #106-97-8). *If swallowed*, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY. Use with adequate ventilation. Avoid breathing spray mist and vapor. Deliberately concentrating and inhaling the vapor of the contents may be harmful or fatal. Avoid frequent or prolonged contact with skin and eyes. For skin contact, wash with soap and water. Provide oxygen or fresh air if overcome by vapor. Do not puncture or incinerate (burn) container. Do not store at temperatures above 120° F. (50° C). Do not place near source of heat, radiator, or in direct sunlight. High temperature may cause the container to burst. *If sprayed in eyes*, flush thoroughly with water for 15 minutes. Get medical help. KEEP OUT OF THE REACH OF CHILDREN

**C-785-A**

**CIM** Supply, Inc. Tom Bing, Jr., 4813 Sardis Road, New Kensington, PA 15068  
Tel: (724) 335-1798 Fax: (724) 337-0788 E-Mail: [tombing@cimsupply.com](mailto:tombing@cimsupply.com)  
[www.cimsupply.com](http://www.cimsupply.com)