

SPECTRUM

Teflon Gel Lubricant

- Lasts longer than conventional lubricants
 - Withstands severe temperatures
- Prevents sticking & freezing of rubber to metal
- Works from -30 degree F to over +600 degree F
 - Prevents rust & corrosion
 - Resists water washout

EXCELLENT ON

Door Hinges ~ Open Gears ~ Wire Ropes w Cables

Chain & Sprockets ~ Conveys ~ Legs on Hoists

Directions

1. Shake aerosol can.
2. Saturate area to be lubricated.
3. If necessary, repeat application.

DANGER: Do not spray near heat, sparks or open flame. Contains Hexane (CAS# 110-54-3), Paraffinic Petroleum Distillates (CAS# 64742-65-0), Propane (CAS# 74-98-6), Isobutane (CAS# 75-28-5), n-Butane (CAS# 106-97-8), Petrolatum (CAS# 8009-03-8), Aliphatic Hydrocarbon (CAS# 64742-63-8). If swallowed, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY. Use with adequate ventilation. Avoid breathing spray mist and vapor. Deliberately concentrating and inhaling the vapor of the contents may be harmful or fatal. Do not puncture or incinerate (burn) container. Do not store at temperatures above 120 degrees F. Do not place near source of heat, radiator or in direct sunlight. High temperatures may cause the container to burst. If sprayed in eyes, flush thoroughly with water for 15 minutes. Get medical help. Read Material Safety Data Sheet before using.

KEEP OUT OF THE REACH OF CHILDREN

**Aerosol
C-530-A**