

TEM-PER

HEAVY DUTY ADHESIVE

- Wide Web Spray
- High Solids
- No Chlorinated Solvents

This wide web spray adhesive is one of the highest performance aerosol adhesives available. For both temporary or permanent bonding, this product is ideal for uneven or porous surfaces and weight materials. Waterproof, flexible, transparent, and non-staining, use this product for your toughest adhesive applications with materials such as leather, cardboard, most plastics, polyethylene sheeting and cloth. Contains no chlorinated solvents or ozone depleters. High solids.

Used On: This versatile adhesive may also be used in upholstery shops, auto upholstery, marinas, sheet metal shops, leather shops, foam shops, labeling (cardboard), hotels, motels (carpet and wallpaper repair) and in the specialized industry of asbestos abatement. This product can be successfully marketed in any industry where strong permanent or temporary adhesion is applicable.

Directions: Always shake well before using. Never aim valve at face. Hold can upright and apply adhesive in a side to side motion 10 to 14 inches from surface.

TEMPORARY BONDS: Spray surface, allow to tack and apply material to be bonded.

PERMANENT BONDS: Liberally spray both surface and material, allow to tack, then apply.

Health Hazard Data: Extremely Flammable. Contains Hexane and Acetone. Use with adequate ventilation. Keep away from heat, sparks, open flame or other ignition sources. Avoid inhalation of spray mist or vapors. If overcome, move patient to fresh air. Call a physician immediately. Avoid contact with eyes and skin. In case of eye contact, flush immediately with water and continue for 15 minutes. If irritation persists, see a physician. For skin contact, wash with soap and water. If irritation persists, call a physician immediately. Do not puncture or incinerate container. Do not store at temperatures above 120°F. **KEEP OUT OF REACH OF CHILDREN.**

Spill Or Leakage Procedures: Absorb with suitable medium. Incinerate or landfill according to local, state, or federal regulations. **DO NOT FLUSH TO SEWER.** Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.

C-235-A