

With Stand

- Concrete Sealer
- Sun Resistant
- Fast Drying
- Easy to Apply
- No Etching Required

Excellent outdoor weather resistance (No Yellowing). Excellent abrasion resistance. Leaves a clear glass-like seamless floor. Excellent adhesion to concrete, metal or wood. Seals pores of the floor. Stops all concrete dusting and prevents spills from becoming stains. Protects floor against acids, alkalis, oils, grease, etc. No etching required. Usually requires only one coat to seal and harden. Fast drying (30 minutes). Floors may be used immediately after drying. Economical-up to 600 sq. ft. per gallon. No pre-mixing required. Traffic lanes can be recoated. Can be applied over tile, paint, terrazzo, and seamless floors. May be applied with low pressure sprayer. Retards moisture. Eliminates need for chemical hardeners, 3 coat applications and scrubbing to remove residue. Ready to use.

Description: Beauty and protection are available in one product. This unique sealer is easier to apply than urethane or epoxy based sealers, yet is as resistant to abrasion and spills. This high gloss, water-clear, protective film dries in about 30 minutes and requires no mixing or measuring. No acid etching is required, but may be desired in some cases. This product eliminates the most common problems with concrete floors: dusting or powdering; stains caused by spillage; erosion caused by acids or chemicals; hairline cracking and flaking.

Where to use: New or old concrete, new or old terrazzo, plaster or mortar surfaces, on stone, brick or quarry tile, machinery or metal surfaces, water tanks or troughs, concrete blocks or pipes, quick dry wood sealer, outdoor sidewalks-concrete benches.

Advantages: Excellent outdoor weather resistance (No Yellowing). Excellent abrasion resistance. Leaves a clear glass-like seamless floor. Excellent adhesion to concrete, metal or wood. Seals pores of the floor. Stops all concrete dusting and prevents spills from becoming stains. Protects floor against acids, alkalis, oils, grease, etc. No etching required. Usually requires only one coat to seal and harden. Fast drying (30 minutes). Floors may be used immediately after drying. Economical-up to 600 sq. ft. per gallon. No pre-mixing required. Traffic lanes can be recoated. Can be applied over tile, paint, terrazzo, and seamless floors. May be applied with low pressure sprayer. Retards moisture. Eliminates need for chemical hardeners, 3 coat applications and scrubbing to remove residue.

Directions: Old or new concrete which is soiled must be thoroughly cleaned and degreased using a heavy-duty detergent/degreaser. Rinse floor with clear water and allow to dry for at least 4 hours. The best sealer adhesion is obtained with surfaces which are as dry as possible. Extremely smooth or "tight" surfaces may require an acid etch prior to product application. Follow label procedure on etching compound.

Application Procedure: After surface has been conditioned, product may be applied using a low pressure sprayer, a string mop, floor squeegee, large paint roller, or large wax applicator. Apply the sealer in a thin, even film at a rate of 500 square feet per gallon. This first coat will penetrate deep into the surface of the concrete to seal and protect. For a deep, glass-like luster, apply a second coat after the first has dried for about 4 to 6 hours.

Maintenance: To maintain this durable, high-gloss appearance, clean floor regularly with a good detergent and water, or for heavy soils, use a detergent/degreaser and water. Rinse well with clear water. For added protection, a floor finish may be applied over this sealer. These procedures will extend the life of the sealed floor surface.

DANGER: Contains Xylene and Toluene. Harmful or fatal if swallowed. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Vapor harmful. Use with adequate ventilation. Avoid prolonged or repeated breathing of vapors. If overcome by fumes, remove victim to fresh air. Resuscitate if necessary. Get medical attention. Flammable. Use only in a well ventilated area. Do not use near heat, sparks, open flame or other sources of ignition. Do not smoke in use area. KEEP OUT OF REACH OF CHILDREN.

Container Disposal: Triple rinse container and discard according to local regulations.

Spill Or Leakage Procedures: WARNING: FLAMMABLE. Eliminate all ignition sources. Handling equipment must be grounded to prevent sparking. Contain spill. Keep out of surface waters & any sewers or water courses entering or leading to surface waters. Soak up with inert absorbent & place in properly labeled

leak-proof containers for disposal.

Product Specifications: Color: None Coverage: 300 - 600 sq. ft./gallon Odor: Aromatic Solvent Lbs./gal.: 7.3 Appearance: Clear % Solids: 20

HMS RATING: Health-2; Flammability-3; Reactivity-0; Personal Protection-B.



Supply, Inc. Tom Bing, Jr., 4813 Sardis Road, New Kensington, PA 15068

Tel: (724) 335-1798 Fax: (724) 337-0788 E-Mail: cimsupply@aol.com